

Stamping Release Color Chart



CR-NAT – Natural



CR-700 – Light Goldenrod




CR-730 – Misty Peach



CR-718 – Terra Cotta



CR-880 – Lavender Blush



CR-430 – Redwood



CR-835 – Red Brick



CR-827 – Sienna



CR-219 – Sandy Buff



CR-300 – Autumn Brown




CR-389 – Dark Brown



CR-395 – Smokey Brown



CR-670 – Powder Blue



CR-675 – Star Blue



CR-923 – Silver




CR-228 – Copper Brown



CR-592 – Slate Green



CR-599 – Seafoam Green



CR-520 – Spring Green



CR-927 – Gray



CR-935 – Charcoal



CR-947 – Dark Gray



CR-960 – Rich Black





Stamping Release Color

Interstar Stamping Release allows a clean and easy release of texturing tools from wet concrete.

It deposits color onto a fresh concrete surface to create a marbled or antiqued effect.

DIRECTIONS

- Step 1.** Place the concrete using recognized methods.
- Step 2.** After the initial floating has been performed and all of the excess bleed water has disappeared, spread the stamping release powder across the surface where the mats will be placed. Stamping release can be spread using the enclosed broadcast bag for a more even dispersal. Simply fill the bag with stamping release powder, then shake it over the concrete surface to distribute the release.
- Step 3.** To further reduce adherence, you may apply some of the release powder directly to the mats. Proceed with stamping immediately after applying the release powder.

FINISHING

- Step 1.** Let the concrete cure for 24 to 36 hours. It is not necessary to use a curing agent or any other method of curing with Interstar Stamping Release. Do not fog or cover the surface during this initial curing period.
- Step 2.** After the curing time has elapsed, use a soft broom to gently sweep away the excess release powder as desired. Dispose of it properly.
- Step 3.** Allow the concrete to cure completely (at least 28 days), and then wash the surface with Interstar's Kopa Stamping Release Cleaner and water.
- Step 4.** For a perfect, long-lasting finish, apply the appropriate Interstar sealer to the clean, dry surface.

IMPORTANT:

This color chart only provides an estimate of the final colors that can be obtained. It is intended to serve as a guideline for color selection, and does not represent the exact colors that will be produced.

MAKE A LASTING IMPRESSION

Interstar Stamping Release imparts color while acting as a bond breaker to prevent stamping mats from sticking to freshly-poured concrete. It is easy to use, permanent and will not fade. Every box is rigorously tested to ensure you receive the premium quality you expect.

SERVICE IS OUR PRIORITY

Our customer service representatives, technicians, chemists and engineers are at your service to assist you with your projects. We pledge to be polite, responsive, flexible and dedicated to your needs.

PACKAGING

Interstar Stamping Release is sold in 30-lb boxes.

SHIPPING

To ensure fast delivery, your order will be shipped from the Interstar distribution center closest to you. Orders are usually shipped the same day.

INFORMATION

For more information about Stamping Release and other Interstar products, please visit our website at www.interstar.ca, contact our Customer Service Department at **800.567.1857** or email info@interstar.ca.

Please see Interstar's warranty for complete details.



www.interstar.ca • 800.567.1857